



COMMERCIAL AUDIO

CURRENT PRODUCT FAMILY · SPECIFICATION SHEET

COM-650 v2

6.5" frameless commercial in-ceiling loudspeaker

WOOFER	6.5" polypropylene cone with rubber surround
TWEETER	0.5" PEI dome
SYSTEM	70 V / 25 V or 8 ohms
POWER HANDLING	100 watts
TRANSFORMER TAPS	20 W, 10 W, 5 W and 2.5 W
FREQUENCY RESPONSE	50 Hz-20 kHz
SENSITIVITY	89 dB
DIMENSIONS	8.86" diameter x 3.54" depth
CUTOUT	7.80"
GRILLE	Frameless, magnetic and paintable

COM-800 v2

8" frameless commercial in-ceiling loudspeaker

WOOFER	8" polypropylene cone with rubber surround
TWEETER	0.5" PEI dome
SYSTEM	70 V / 25 V or 8 ohms
POWER HANDLING	120 watts
TRANSFORMER TAPS	32 W, 16 W, 8 W and 4 W
FREQUENCY RESPONSE	35 Hz-20 kHz
SENSITIVITY	89 dB
DIMENSIONS	10.75" diameter x 4.10" depth
CUTOUT	9.30"
GRILLE	Frameless, magnetic and paintable

COM-600

Pendant loudspeaker

DRIVER	6" full-range driver
MOUNTING	Suspended pendant with steel safety wire
DISTRIBUTED AUDIO	70 V / 100 V
TRANSFORMER	Built-in step-down transformer with three taps
POWER TAP	Up to 7.5 W
FREQUENCY RESPONSE	150 Hz-14 kHz
SENSITIVITY	92 dB