

HIGH-DEFINITION ARCHITECTURAL AUDIO

ELITE SERIES

UPGRADED MATERIALS. MORE DETAIL.

The DITO ELITE Series uses upgraded driver materials for more demanding music and home entertainment systems. Standard, angled and stereo-input configurations give professional installers the flexibility to address critical listening positions and specialized rooms.

CURRENT MODELS

ELI-650 v2

6.5-inch high-definition model for premium distributed audio.

ELI-800 v2

8-inch high-definition model with greater low-frequency extension.

ELI-650A v2

Angled LCR model designed to direct sound toward the listening area.

ELI-650S v2

Single-speaker configuration for applications requiring flexible placement.



VERIFIED TECHNICAL INFORMATION

COMPARE THE CURRENT FAMILY

SPECIFICATION	ELI-650 v2	ELI-800 v2	ELI-650A v2	ELI-650S v2
CONFIGURATION	Two-way in-ceiling	Two-way in-ceiling	Two-way angled LCR in-ceiling	Two-way in-ceiling
WOOFER	6.5-inch fiberglass	8-inch fiberglass, rubber surround	6.5-inch composite carbon fiber, 15-degree angle	6.5-inch polypropylene, butyl surround
TWEETER	1-inch pivoting titanium dome	1-inch pivoting titanium dome	1-inch pivoting aluminum dome	Directional soft dome
POWER HANDLING	150W	150W	90W	40W - 100W
IMPEDANCE	8 ohms	8 ohms	8 ohms	8 ohms
FREQUENCY RESPONSE	40 Hz - 20 kHz	35 Hz - 20 kHz	45 Hz - 20 kHz	50 Hz - 20 kHz
SENSITIVITY	Not specified	Not specified	89 dB	Not specified
CONNECTIONS	Not specified	Five-way binding posts	Gold-plated five-way binding posts	Not specified
PRESENTATION	Pair	Pair	Each	Each