



INSTALLATION ACCESSORIES

CURRENT PRODUCT FAMILY · SPECIFICATION SHEET

FMW-900.600 v2

Full-motion display mount

DISPLAY SIZE	60-100"
LOAD CAPACITY	80 kg / 176 lb
VESA	200 x 200 to 900 x 600
SWIVEL	±45°
POST-INSTALLATION LEVELING	±3°
MOVEMENT	Swivel, tilt, rotation and extension
WALL TYPES	Concrete, brick or wood framing

TOS-3

3-foot optical digital audio cable

CONNECTION	Toslink optical digital
LENGTH	3 ft
CONSTRUCTION	Flexible jacket with molded strain relief
CONNECTORS	Full-size Toslink male to male
FINISH	Black

TOS-6

6-foot optical digital audio cable

CONNECTION	Toslink optical digital
LENGTH	6 ft
CONSTRUCTION	Flexible jacket with molded strain relief
CONNECTORS	Full-size Toslink male to male
FINISH	Black

TOS-12

12-foot optical digital audio cable

CONNECTION	Toslink optical digital
LENGTH	12 ft
CONSTRUCTION	Flexible jacket with molded strain relief
CONNECTORS	Full-size Toslink male to male
FINISH	Black

TOS-25

25-foot optical digital audio cable

CONNECTION	Toslink optical digital
LENGTH	25 ft
CONSTRUCTION	Flexible jacket with molded strain relief
CONNECTORS	Full-size Toslink male to male
FINISH	Black

TOS-50

50-foot optical digital audio cable

CONNECTION	Toslink optical digital
LENGTH	50 ft
CONSTRUCTION	Flexible jacket with molded strain relief
CONNECTORS	Full-size Toslink male to male
FINISH	Black

PRO-WPW

Brush cable pass-through wall plate

FORMAT	Single-gang, white
COMPATIBILITY	Single-gang electrical J-boxes and low-voltage mounting boxes
BRUSH OPENING	Approximately 3/4 x 2-1/8 in
PURPOSE	Organized bulk AV cable routing
PRESENTATION	5-pack
INCLUDED	Trim plate and color-matched mounting screws

PRO-CCO

Adjustable ceiling and drywall circle cutter

CUT DIAMETER	1.2-11.8"
MAXIMUM DEPTH	1.25"
MATERIALS	Drywall and ceiling tile
CUTTERS	Balanced dual-blade design with carbide-tipped and high-speed steel blades
DUST CONTROL	Integrated 14.25-inch shield with bearing collar
INCLUDED	Case, spare blades, arbor bits, drill bits, tape measure and pencil
NOT INTENDED FOR	Concrete or hardwood

PRO-T

70 V / 100 V line-matching transformer

FREQUENCY RESPONSE	20 Hz-20 kHz ± 1 dB
PRIMARY TAPS	20 W, 15 W, 10 W and 5 W
SECONDARY IMPEDANCE	8 or 4 ohms
INSERTION LOSS	1 dB
LEAD LENGTH	6"
DIMENSIONS	3.37" W x 2" D x 2" H
MOUNTING	Self-adhesive mounting pad included