

Indoor/Outdoor

Congratulations! You have purchased a high quality stereo loudspeaker. When matched to comparable electronic equipment, expect years of quality high fidelity sound. Our belief is that music matters and we are focused on delivering superlative music reproduction everywhere in your home.

The following manual is designed to give you, the installer or owner, basic information as to the speaker's installation and operation. It is beyond the scope of this manual to go into all the details that must be taken into consideration in a sophisticated high fidelity system.

If you have any questions regarding this speaker which are not answered by this manual, contact your local dealer for assistance. For the most current information please visit www.ditopro.com.

KEY FEATURES

- Durable All-Weather Construction
- 70V/100V Transformer for Commercial Applications
- Tap Settings
 - 70V: 8 ohm, 30W, 15W, 7.5W, 3.8W
 - 100V: 8 ohm, 30W, 15W, 7.5W
- Resilient All Weather Drivers
- Includes Surface Mount Bracket, Pendant Hardware, and 8" Ground Stake.



ACOUSTIC SPECIFICATIONS

- 6.5" All Weather PP Woofer.
- 1" PEI Dome Tweeter.
- 50W RMS.
- 87db SPL.
- Impedance 8Ω / 70V / 100V.
- Frequency Response 100Hz – 20kHz +/- 3dB

MECHANICAL SPECIFICATIONS

- Width: 8.1" (169mm)
- Height: 11.5" (240mm)
- Depth: 10.4" (244mm)
- Product Weight: 7.5 lbs (3.4KG)

